

# 燃气型自动干衣机 GQZ系列

## GQZ Series Automatic Dryer Gas Heating



- 1 适应性和经济性**  
15kg一罐液化气（相当于22m<sup>3</sup>天然气）即可烘干200多公斤织物，烘干每公斤织物的燃气成本只有约0.75元。
- 2 烘干效率**  
大叶片风叶，特殊的风道结构，开孔密度大的专用转笼，通风顺畅，热交换效率高，烘干速度快。
- 3** 加热点火与温度检测联动、自动控制，方便高效。
- 4 燃气组件**  
采用专用燃烧器。燃烧充分，被烘织物无发灰之虞。
- 5 燃气安全性**  
采用自动温控，自动点火，火焰检测，熄火保护及自动报警，室内排风扇联动等措施，多方位保证了燃烧器的使用安全性。
- 6 控制器**  
高速度微处理器，轻触面板，反应迅速，操作方便，密封性好，防水，防尘。具有5套自动程序，自动运行时，允许手动干预。
- 7 装衣门**  
大直径装衣门及180°平开门结构，人性化设计，装料出料方便，省力。
- 8 毛绒收集器**  
抽屉式的毛绒收集器，清理方便快捷。一体化成型，无清理死角，耐用/美观。
- 9 转笼**  
高密度的网孔，通风率高，烘干速度快。采用小窝孔网眼，防止布草磨损和钩丝，延长布草的使用寿命。优质不锈钢制作，美观/结实/耐用。

- 1 Economical**  
15KG Tank liquefied petroleum gas (equals to 22m<sup>3</sup> nature gas) can dry more than 200 kilograms of linens, and the gas cost is about 0.75 RMB/kg.
- 2 Drying efficiency**  
Big fan blade, special air duct, matching with high density mesh,ensure good ventilation, high heat exchange efficiency,fast drying.
- 3** Fire ignition and temperature detection interlocked, automatic control, convenient and efficient.
- 4 Gas parts**  
Customized burner. Gas fully burned, no risk of linens turning black.
- 5 Gas safety**  
Automatic temperature control, automatic ignition, flame check,flame-out protection, indoor fan ventilation, all above endure the gas burner operation safety.
- 6 Controller**  
High speed micro processor,soft touch,quick response,easy operation,well sealed,waterproof,dustproof.5 preset programs, automatic and manual operation switchable.
- 7 Door**  
Large diameter, and can be open 180 degree, user friendly,easy loading and unloading.
- 8 Lint collector**  
Drawer-type lint collector,easy to clean. Integrated molding,durable and beautiful.
- 9 Inner drum**  
High intensity mesh,high ventilation rate,fast drying speed. Small hole mesh to prevent abrasion and snagging, extending linens service life. Premium stainless steel,beautiful strong and durable.



- ▲ 专业级控制器，5套自动程序，操作方便，稳定可靠。
- ▲ Professional controller with 5 preset program,easy to operate, stable and reliable.




- ▲ 专用燃烧器，自动温控，熄火保护及自动报警，使用一次能源，节能、高效。
- ▲ Special burner, automatic temperature control, flame-out protection and automatic alarm, using primary energy, energy-saving and efficient.



- ▲ 抽屉式毛绒收集器，清理无死角，方便、实用。
- ▲ Drawer-type lint collector is easy and convenient to clean.



- ▲ 特有的直接冷风装置，可快速冷却被烘织物，防止面料质变。
- ▲ Special direct cold wind device, fast cooling linens, anti linens qualitative change.



- ▲ 门控安全联动和红色蘑菇头急停开关组合，保证安全运行，杜绝生产事故。
- ▲ Door safety control lock together with red mushroom emergency button ensure machine safe running, prevent incident.



- ▲ 规范接线，线号管和图纸线号一一对应，标号清晰，方便故障排查及维护。
- ▲ Standard wiring connection, wiring tube number clearly matches with the number on the drawing, easy to do troubleshooting and maintenance.

### 产品参数 (Parameters)

型号/参数	Type/Parameter	单位 Unit	GQZ-15	GQZ-30	GQZ-50	GQZ-70	GQZ-100	GQZ-100T
额定容量	Capacity	kg	15	30	50	70	100	100
滚笼尺寸 (直径×深度)	Drum Diameter (diameter x depth)	mm	Φ800×600	Φ940×870	Φ1150×970	Φ1270×1100	Φ1450×1220	Φ1450×1220
主电机功率	Motor Power	kW	0.37	0.75	1.1	1.5	2.2	2.2
风机功率	Fan Power	kW	0.37	0.55	1.5	1.5	1.5×2	1.5×2
折合电功率	Converted Electric Power	kW	15	28	45	45	76	76
额定电压	Rated Voltage	v	380	380	380	380	380	380
燃气压力	Gas Pressure	kPa	8-10	8-10	8-10	8-10	8-10	8-10
燃气耗量 (天然气)	Gas Consumption (natural gas)	m <sup>3</sup> /h	1.4	2.8	4.5	6.3	9	9
排风管接口	Ventilation Joint	mm	Φ230	Φ285	Φ300	Φ350	Φ430	Φ430

### 外形尺寸 (Dimension)

宽	Width	mm	920	1070	1270	1390	1580	1700
深	Depth	mm	1100	1410	1530	1720	1930	2000
高	Height	mm	1810	2000	2670	2800	2890	3120
重量	Weight	kg	350	500	670	860	1100	1250